2025-04-06-18-02 1/4 Quake 3 Arena Cvars

Quake 3 Arena Cvars

Here is a selection of the configuration variables (cvars) for Quake III Arena:

Cvar	Description
bot_minplayers	sets the minimum number of players on the server, when fewer clients are connected, the server will spawn as many bots as needed to bring the total number of player plus bots to this value, when clients connect, bots will be kicked to make room
capturelimit	Capture limit at which the map ends, only affects CTF matches
cl_guidserveruniq	makes cl_guid unique for each server
cl_lanforcepackets	if this is enabled and dedicated mode is not 2, clients on your same subnet will ignore the "rate" value and will get all the "snapshots" the server will elaborate
cl_motd	enables message of the day
cl_motdstring	content of the message of the day
dedicated	Is the server a dedicated server? <i>listen server</i> (accessible via internet, not announced) = 0 , <i>internet server</i> (announced) = 1 , <i>LAN server</i> (not reachable via internet) = 2
dmflags	no falling damage = 8, fixed field of vision = 16 and footsteps = 32, sums are allowed.
fraglimit	set fraglimit on a server (0 is no limit)
g_allowvote	toggle the use of voting on a server
g_arenasfile	sets the file name to use for map rotation and bot names and game type for each arena (default: scripts/arenas.txt within the pk3 file)
g_banips	ban specified tcp/ip address from connecting to your server
g_blueteam	set the icon for the blue team
g_botsfile	sets the file name to use for setting up the bots configuration and characters for each bot (default: scripts/bots.txt within the pk3 file)
g_delaghitscan	compensate network latency effects when using "hitscan" (instant hit, such as the machinegun) weapons, for all the clients which will require it
g_dowarmup	toggle the use of a warmup period before a match game
g_enablebreath	breathing effect (0: off, 1: on)
g_enabledust	dust effect by feet on particular maps (0: off, 1: on)
g_filterban	toggle the banning of players that match a certain criteria/filter
g_forcerespawn	Number of seconds until a client is automatically respawned, unless the client does it by itself. Set it to 0 to disable force respawn.
g_friendlyfire	toggle damage caused by friendly fire (0: off, 1: can kill or injure teammate)
g_gametype	sets the server game type (0: classic deathmatch, 1: tournament one-on-one play, 3: team deathmatch, 4: ctf)
g_gravity	game severity (usually set by map properties)
g_inactivity	time limit that a player can be still before being expelled
g_knockback	amount of movement when impacted by rocket/bfg/plasma
g_listentity	display of map entities by number
g_log	file name for logging game data or statistics
g_logsync	toggle the logging to append to the existing file and not overwrite

Cvar	Description
g_maxgameclients	set maximum # of players who may join the game, the remainder of clients are forced to spectate
g_motd	set message of the day
g_needpass	Activates or deactivates the server password requirement $(0 = off, 1 = on)$
g_password	set the serverside password players have to use to get on the server
g_quadfactor	damage multiplier for the quad powerup (1: no quad damage powerup)
g_redteam	set the icon for the red team
g_smoothclients	enable players to use cg_smoothclients on the server
g_speed	movement speed of players
g_synchronousclients	synchronizes all clients to allow demo recording on the server, which may decrease netplay performance
g_teamautojoin	toggle the automatic joining of the smallest or loosing team
g_teamforcebalance	toggle the forcing of teams to be as even as possible on a server
g_warmup	the warmup time for tournament play
g_weaponrespawn	set the number of seconds between the time a weapon is picked up and when it respawns
g_weaponteamrespawn	set the number of seconds between the time a weapon is picked up and when it respawns on team matches
logfile	enable server log file
net_ip	set the ip of the network card to be used by your server, not used in ioQuake derivatives
net_mcast6addr	Sets the multicast address to be used for LAN server discovery. Default is ff04::696f:7175:616b:6533
net_port	set external port of your server
net_port6	set external port of your server on ipv6
net_qport	the source port your client utilizies
password	set password
protocol	game version, e.g. 40
r_logFile	0
rconaddress	set remote console address
rconpassword	set rcon password for remote operation from a client connected to the server. client must store the correct password in the rconpassword variable before they can issue console commands to the server preceded by "rcon"
sv_allowDownload	Are uploads to the clients allowed? $1 = yes$, $0 = no$
sv_cheats	allows cheats
sv_dlurl	the base of the http or ftp site that holds custom pk3 files for your server
sv_floodprotect	toggle server flood protection to keep players from bringing the server down
sv_fps	set server fps
sv_hostname	set the name of the server
sv_keywords	set list of keywords for server browsers that support searching server lists
sv_killserver	Are clients able to issue a <i>killserver</i> command? $1 = yes$, $0 = no$
	if this is enabled and dedicated mode is not 2, clients on your same subnet will ignore the "rate" value and will get all the "snapshots" the server will
sv_lanforcerate	elaborate
sv_lanforcerate sv_mapchecksum	

2025-04-06-18-02 3/4 Quake 3 Arena Cvars

sets the number of client slots to reserve for those clients who know the sv_privateclients sv_privateclients sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server	Cvar	Description
sy_master4 set url or address to optional master server 4 sy_master5 set url or address to optional master server 5 sv_maxclients maximum number of people allowed to join the server dedicated server memory optimizations sv_maxping set the maximum ping allowed on the server to keep high ping players out option to force all clients to play with a max rate, this can be used to limit the advantage of low ping players or to cap bandwidth utilization for a server sv_mainping set the minimum ping allowed on the server to keep low ping players out sy_minrate set the minimum rate allowed on the server sy_nopredict May the client use predictions? 1 = no, 0 = yes sv_packetdelay simulate packet latency (0: off) sv_padpackets force server to pad snapshot packets sv_paknames names of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_pure userver (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_reconnectlimit set server reconnect limit sv_referencedpaknames sw_referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_server id set server imeout time in seconds sv_sineout set server imeout time in second	sv_master2	set url or address to optional master server 2
sv_master5 sv_maxclients maximum number of people allowed to join the server dedicated server memory optimizations sv_maxping set the maximum ping allowed on the server to keep high ping players out option to force all clients to play with a max rate, this can be used to limit the advantage of low ping players or to cap bandwidth utilization for a server sv_minping set the minimum ping allowed on the server to keep low ping players out server sv_mopredict sv_maxclients sv_paperdict May the client use predictions? 1 = no, 0 = yes sv_packetdelay simulate packet latency (0: off) sv_padpackets force server to pad snapshot packets sv_paknames names of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_pure sv_privatepassword and requires all clients to use the password command with the correct password and requires all clients to use the password command with the correct password to join the server sv_reconnectlimit sv_referencedpaknames sv_referencedpaks checksums of the referenced pk3 files sv_renning server reconnect limit sv_referencedpaks checksums of the referenced pk3 files sv_renning server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_combetime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_master3	set url or address to optional master server 3
maximum number of people allowed to join the server dedicated server memory optimizations sv_maxping set the maximum ping allowed on the server to keep high ping players out option to force all clients to play with a max rate, this can be used to limit the advantage of low ping players or to cap bandwidth utilization for a server sy_minping set the minimum ping allowed on the server to keep low ping players out sy_minping set the minimum rate allowed on the server sy_nopredict May the client use predictions? 1 = no, 0 = yes sv_packetdelay simulate packet latency (0: off) sv_padpackets force server to pad snapshot packets sv_paknames names of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_reconnectlimit set server reconnect limit sv_referencedpaks checksums of the referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_restituted check cd-key on clients sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_master4	set url or address to optional master server 4
memory optimizations sv_maxping set the maximum ping allowed on the server to keep high ping players out option to force all clients to play with a max rate, this can be used to limit the advantage of low ping players or to cap bandwidth utilization for a server sv_minping set the minimum ping allowed on the server to keep low ping players out sv_minrate set the minimum rate allowed on the server sv_nopredict May the client use predictions? 1 = no, 0 = yes sv_packetdelay simulate packet latency (0: off) sv_padpackets force server to pad snapshot packets sv_paknames names of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server sv_privatepassword set server possible to prevent cheating) sv_reconnectlimit set server reconnect limit sv_referencedpaknames sv_referencedpaknames sv_referencedpakas sv_referencedpaks checksums of the referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_referencedpaks set server id set server id set server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sy_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_master5	set url or address to optional master server 5
option to force all clients to play with a max rate, this can be used to limit the advantage of low ping players or to cap bandwidth utilization for a server sv_minping set the minimum ping allowed on the server to keep low ping players out sy minrate set the minimum rate allowed on the server sv_nopredict May the client use predictions? 1 = no, 0 = yes sv_packetdelay simulate packet latency (0: off) sv_padpackets force server to pad snapshot packets sv_padhames names of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privateclients sv_privateclients sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_reconnectlimit set server reconnect limit sv_referencedpaknames names of the referenced pk3 files sv_renormediames checksums of the referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_reserverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_maxclients	· · ·
sv_maxrate	sv_maxping	set the maximum ping allowed on the server to keep high ping players out
sy_minrate set the minimum rate allowed on the server sy_nopredict May the client use predictions? 1 = no, 0 = yes sy_packetdelay simulate packet latency (0: off) sy_padpackets force server to pad snapshot packets sy_paknames names of the loaded pk3 files, only active, when sy_pure is set to 1 sy_paks checksums of the loaded pk3 files sy_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sy_privateclients sy_maxclients minus sy_privateclients equals the number of public connect slots set server password and requires all clients to use the password command with the correct password to join the server sy_pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sy_referencedpaknames names of the referenced pk3 files sy_referencedpaks checksums of the referenced pk3 files sy_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sy_serverid set server id sy_showloss enable sever packet loss display sy_strictauth check cd-key on clients sy_timeout set server timeout time in seconds sy_voip ioq3: enables voip set seams game flag timelimit amount of time before new map loads or next match begins	sv_maxrate	the advantage of low ping players or to cap bandwidth utilization for a
sv_nopredict sv_packetdelay simulate packet latency (0: off) sv_padpackets force server to pad snapshot packets sv_paknames names of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privateclients sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server sv_pure pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_referencedpaknames sv_referencedpaknames names of the referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_reverid set server id sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_minping	set the minimum ping allowed on the server to keep low ping players out
sw_packetdelay simulate packet latency (0: off) sv_padpackets force server to pad snapshot packets sv_paks names of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privateclients sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server sv_pure pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_reconnectlimit set server reconnect limit sv_referencedpaknames names of the referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_renning server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_minrate	set the minimum rate allowed on the server
sv_padpackets force server to pad snapshot packets sv_paknames names of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privateclients sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server sv_pure pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_referencedpaknames set server reconnect limit sv_referencedpaks checksums of the referenced pk3 files sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_nopredict	May the client use predictions? $1 = no$, $0 = yes$
sv_paks names of the loaded pk3 files, only active, when sv_pure is set to 1 sv_paks checksums of the loaded pk3 files sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server sv_pure pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_referencedpaknames sv_referencedpaknames names of the referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_packetdelay	simulate packet latency (0: off)
sv_paks shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privateclients sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server sv_pure pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_reconnectlimit set server reconnect limit sv_referencedpaknames checksums of the referenced pk3 files sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set seam game flag timelimit amount of time before new map loads or next match begins	sv_padpackets	force server to pad snapshot packets
sv_paused shows pausing state of the server, read-only, not used on ioQuake any more sets the number of client slots to reserve for those clients who know the sv_privateclients sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server sv_pure pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_reconnectlimit set server reconnect limit sv_referencedpaknames of the referenced pk3 files sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_paknames	names of the loaded pk3 files, only active, when sv_pure is set to 1
sets the number of client slots to reserve for those clients who know the sv_privateclients sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server sv_pure pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_reconnectlimit set server reconnect limit sv_referencedpaknames names of the referenced pk3 files sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set sem game flag timelimit amount of time before new map loads or next match begins	sv_paks	checksums of the loaded pk3 files
sv_privateclients sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect slots sv_privatepassword set server password and requires all clients to use the password command with the correct password to join the server sv_pure pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating) sv_reconnectlimit set server reconnect limit sv_referencedpaknames names of the referenced pk3 files sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_paused	shows pausing state of the server, read-only, not used on ioQuake any more
with the correct password to join the server sv_pure	sv_privateclients	sv_privatepassword and have entered it in their "password" variable. sv_maxclients minus sv_privateclients equals the number of public connect
sv_reconnectlimit set server reconnect limit sv_referencedpaknames names of the referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_privatepassword	
sv_referencedpaks names of the referenced pk3 files sv_referencedpaks checksums of the referenced pk3 files sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags timelimit amount of time before new map loads or next match begins	sv_pure	pure server (0: off, 1: the server will check to make sure clients have "pure" (unaltered) pk3 files to prevent cheating)
sv_referencedpaks checksums of the referenced pk3 files sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags sets team game flag timelimit amount of time before new map loads or next match begins	sv_reconnectlimit	set server reconnect limit
sv_running server status: Running as a server, but is a map loaded? 1 = yes, 0 = no sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags sets team game flag timelimit amount of time before new map loads or next match begins	sv_referencedpaknames	names of the referenced pk3 files
sv_serverid set server id sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags sets team game flag timelimit amount of time before new map loads or next match begins	sv_referencedpaks	checksums of the referenced pk3 files
sv_showloss enable sever packet loss display sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags sets team game flag timelimit amount of time before new map loads or next match begins	sv_running	server status: Running as a server, but is a map loaded? $1 = yes$, $0 = no$
sv_strictauth check cd-key on clients sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags sets team game flag timelimit amount of time before new map loads or next match begins	sv_serverid	set server id
sv_timeout set server timeout time in seconds sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags sets team game flag timelimit amount of time before new map loads or next match begins	sv_showloss	enable sever packet loss display
sv_voip ioq3: enables voip sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags sets team game flag timelimit amount of time before new map loads or next match begins	sv_strictauth	check cd-key on clients
sv_zombietime set inactivity time before clients (zombies) are disconnected teamflags sets team game flag timelimit amount of time before new map loads or next match begins	sv_timeout	set server timeout time in seconds
teamflags sets team game flag timelimit amount of time before new map loads or next match begins	sv_voip	ioq3: enables voip
timelimit amount of time before new map loads or next match begins	sv_zombietime	set inactivity time before clients (zombies) are disconnected
	teamflags	sets team game flag
username set username	timelimit	amount of time before new map loads or next match begins
	username	set username

[Quake 3 Arena] [Games Database]

 $Last \ update: \\ 2023-04-06-19-57 \ en: games: quake_3_arena_cvars \ https://mwohlauer.d-n-s.name/wiki/doku.php?id=en: games: quake_3_arena_cvars \& rev=1680811029 \ arena_cvars \& rev=1$

From:

https://mwohlauer.d-n-s.name/wiki/ - mwohlauer.d-n-s.name / www.mobile-infanterie.de

https://mwohlauer.d-n-s.name/wiki/doku.php?id=en:games:quake_3_arena_cvars&rev=1680811029

Last update: 2023-04-06-19-57

